

描述 / Descriptions

TO-252 塑封封装 N 沟道 MOS 场效应管。

N-CHANNEL MOSFET in a TO-252 Plastic Package.

特征 / Features



阻抗低，开关速度快。无卤产品。

Low On-Resistance, fast switching. Halogen-free Product.

用途 / Applications

用于高效 DC/DC 转换和功率开关。

These devices are well suited for high efficiency switching DC/DC converters and switch mode power supplies.

内部等效电路 / Equivalent Circuit**引脚排列 / Pinning**

PIN1 : G

PIN 2 : D

PIN 3 : S

PIN 4 : D

放大及印章代码 / h_{FE} Classifications & Marking

见印章说明。 See Marking Instructions.

极限参数 / Absolute Maximum Ratings(Ta=25°C)

参数 Parameter		符号 Symbol	数值 Rating	单位 Unit
Drain-Source Voltage		V_{DSS}	100	V
Drain Current		$I_D(T_C=25^{\circ}\text{C})$	59	A
Pulsed Drain Current		I_{DM}	240	A
Gate-Source Voltage		V_{GSS}	± 20	V
Avalanche Current		I_{AR}	15	A
Single Pulsed Avalanche Energy		E_{AS}	170	mJ
Total Power Dissipation		$P_D(T_C=25^{\circ}\text{C})$	73	W
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	$^{\circ}\text{C}$
Junction-to-Ambient	$t \leq 10\text{s}$	$R_{\theta JA}$	20	$^{\circ}\text{C/W}$
Junction-to-Ambient	Steady-State		50	
Junction-to-Case	Steady-State	$R_{\theta JC}$	1.7	

电性能参数 / Electrical Characteristics(Ta=25°C)

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0\text{V}$ $I_D=250\mu\text{A}$	100	102		V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=100\text{V}$ $V_{GS}=0\text{V}$			1	μA
		$V_{DS}=100\text{V}$ $V_{GS}=0\text{V}$ $T_J=125^{\circ}\text{C}$			5	μA
Gate-Body Leakage Current	I_{GSS}	$V_{GS}=\pm 20\text{V}$ $V_{DS}=0\text{V}$			± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu\text{A}$	2.0	2.6	4.0	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10\text{V}$ $I_D=35\text{A}$		14	18	m Ω
Diode Forward Voltage	V_{SD}	$V_{GS}=0\text{V}$ $I_S=35\text{A}$ $T_J=25^{\circ}\text{C}$			1.3	V

电性能参数 / Electrical Characteristics(Ta=25°C)

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Input Capacitance	C_{iss}	$V_{DS}=25V$ $V_{GS}=0V$ $f=1MHz$		4780		pF
Output Capacitance	C_{oss}			110		
Reverse Transfer Capacitance	C_{rss}			140		
Gate resistance	R_g	$V_{GS}=0V$, $V_{DS}=0V$, $f=1MHz$		1		Ω
Total Gate Charge	$Q_{g(10V)}$	$V_{GS}=10V$, $V_{DS}=50V$, $I_D=20A$		16		nC
Gate Source Charge	Q_{gs}			5		
Gate Drain Charge	Q_{gd}			3		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=50V$ $R_L=2.5\Omega$ $R_{GEN}=3\Omega$		7.5		ns
Turn-On Rise Time	t_r			2.5		
Turn-Off Delay Time	$t_{d(off)}$			16.5		
Turn-Off Fall Time	t_f			3		

电参数曲线图 / Electrical Characteristic Curve




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

电参数曲线图 / Electrical Characteristic Curve




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area





Figure 10: Normalized Maximum Transient Thermal Impedance

外形尺寸图 / Package Dimensions




单位: mm

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
A	2.20	2.40	E	5.95	6.25
B	0.95	1.25	e1	2.24	2.34
b	0.50	0.70	e2	4.43	4.73
b1	0.45	0.55	L1	9.45	9.95
C	0.45	0.55	L2	1.25	1.75
D	6.45	6.75	L3	0.60	0.90
D1	5.10	5.50	K	0.00	0.10

TQ-252

印章说明 / Marking Instructions



说明：

BR： 为公司代码

3710： 为产品型号


****： 为生产批号代码，随生产批号变化。

Note:

BR: Company Code

3710: Product Type.

****: Lot No. Code, code change with Lot No.

回流焊温度曲线图(无铅) / Temperature Profile for IR Reflow Soldering(Pb-Free)


说明：

- 1、预热温度 150 ~ 180°C，时间 60 ~ 90sec;
- 2、峰值温度 255±5°C，时间持续为 5±0.5sec;
- 3、焊接制程冷却速度为 2 ~ 10°C/sec.

Note:

- 1.Preheating:150~180°C, Time:60~90sec.
- 2.Peak Temp.:255±5°C, Duration:5±0.5sec.
3. Cooling Speed: 2~10°C/sec.

耐焊接热试验条件 / Resistance to Soldering Heat Test Conditions

温度：270±5°C

时间：10±1 sec.

Temp.:270±5°C

Time:10±1 sec

包装规格 / Packaging SPEC.

卷盘包装 / REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
TO-252	2,500	2	5,000	5	25,000	13" ×16	360×360×50	385×257×392

套管包装 / TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

使用说明 / Notices